MY WATER FEELS SANDY OR GRITTY							
LIKELY PROBLEM	HEALTH CONCERN?	OTHER CLUES & CONSIDERATIONS	CONFIRM IT	POSSIBLE FIXES	LICENSE REQUIRED FOR FIX?	STATE FUNDS?	MORE INFO
Sand or Silt from: an improperly developed well; an increase in pumpage; a sandstone well with a sloughing formation; or screen failure due to excessive incrustation	Although silt/sand is a nuisance because it can shorten the life of water using appliances and damage your well pump. The to se to	Is this a new well? Did the driller develop the well properly? Was the screen sized properly to prevent fine materials from entering the well? Did silt/sand increase in your water following installation of a larger pump? Did you recently install a water fixture that uses large amounts of water? If you are pumping more water than before from a sandstone well, water can scour the open drillhole causing sand to	Fill a glass or the bathtub, and let the water sit for awhile. Does sand drop to the bottom?	For a new well: Let the water run for a couple days. Sometimes this will clear out the fine materials. If this doesn't work contact your driller and request that he return to develop the well and/or determine what is causing the sand problem. Install a liner in a sandstone well.	Yes, Well Drillers are required to develop the well properly after drilling. Yes, Well Drillers have the knowledge and equipment to install	No	Contact a licensed Well Driller
		the sand increased gradually as water production has decreased? Maybe the screen has become incrusted so that water enters the well at higher velocities and erodes larger holes in the		A liner can seal off a sloughing sandstone formation to keep sand/silt out of the water. Replace the screen in a sand & gravel well; or install a screen if there is none.	Yes, <u>Well Drillers</u> have the knowledge and equipment to replace well screens.	No	